



Ultra-high Speed HDD Eraser (4ports)

SA330

30 GB/min.
Copy Speed

SA330 SAS HDD/SSD sanitizer lets you easily erase many types of interfaces via optional adapters to greatly enhance the efficiency. The built-in 7 main data erasure modes comply with NIST SP 800-88r1 and DoD 5220-M standards. It facilitates sanitization of HDD/SSD without the need of a computer and software and the transfer speed is up to 30 GB per minute.

In addition to data sanitization, it has 4 kinds of data duplication modes, including Systems & Files, Whole Media, All Partitions and Percentage % Copy.

Features

Various HDD data Erasure tools

6 Sanitization Modes: Full Erase(1-Pass Erase), DoD Erase, DoD Erase+Compare, 7-Pass Erase, Secure Erase, and Enhanced Secure Erase. Erase Functionality Compliant with NIST SP 800-88r1 and DoD 5220-M Standards

Ultra-high Speed of up to 30 GB /min

Conforms to SAS and SATA Revision 3.0 specification and achieves the maximum transfer speed of 30 GB per min.. The actual speed performance varies by storage media.



User Interface | No PC Required

The equipment is operated without the need of a computer and software. Users can quickly grasp the status by using the four keys to select the functions, and along with independent LED indication on each port..

1

Website: www.ureach.in E-mail: info@ureach.in

U-Reach India



Supports more interfaces with matching adapters

Supports all kinds of brands in the 2.5 "/3.5" SATA hard disks and solid state disks. Support IDE, iVDR, eSATA, mSATA SSD, M.2(NGFF), CFast and other interfaces via optional adapters

HDD Hardware Protection Design

Select the function you want, and the duplicator will power the HDD .It will also cut off the power after the task is completed. This is to avoid unplugging the HDD from the duplicator when the power is still on. The safety measures taken excel over hot swapping

Product Models

Photo	Model	Targets	Product Size	Package Dimensions	Product Weight
minSAS	SA330	1:3	30 x 15 x 14.5 (cm)	47 x 40 x 38 (cm)	7.35 kg

Standard Package



SA330 Duplicator x 1



12V Power Adapter x 1



Power Cord x 1



User Manual x 1

Optional Package



mSATA to SATA Adapter-P1041



M.2(NGFF) to SATA Adapter-P1051



CFast to SATA Adapter-P1053

2

Website: www.ureach.in E-mail: info@ureach.in

U-Reach India



Specifications

Bandwidth Performance	30 GB / min. *Actual performance is dependent on device transfer speeds*
Sanitization Modes	 Full Erase (NIST 800-88) DoD3 Pass (DoD 5220.22-M) DoD3 Pass+Compare (DoD 5220.22-M) DoD7 Pass [DoD 5220.22-M(ECE)] Secure Erase (NIST 800-88) Enhanced Secure Erase
Supported Capacity	Over 18TB+.
Operation Mode	Standalone, FPGA-based Operation

Advanced Functions

Copy Modes	Systems & Files, Whole Media, All Partitions, Percentage % Copy
Supported Formats	Quick Copy (System and Files): FAT16/32, exFAT, Windows (NTFS), Linux (Ext2/Ext3/Ext4), and Mac (HFS/HFS+/HFSX) Whole Media Copy: All formats.
Compare Function	Bit-by-bit data comparison

Hardware Specifications

LCD Display	2x20 Backlit Monochrome LCD Display		
LEDs	2 LED (Red/Green) Indicators per Port		
Control Panel	4 Push Buttons (▲, ▼, OK, ESC)		
Power Requirements	12V DC Adaptor		
Temperature	Working: 0°C ~ 60°C	Storage: -20°C ~ 85°C	
Humidity	Working: 20% ~ 80%	Storage: 5% ~ 95%	
Certifications	FCC, CE, RoHS, and Reach		

^{***}Specifications are subject to change without further notice.

Website: www.ureach.in E-mail: info@ureach.in