

MTS-SAS Series: SAS /SATA Hard Disk and SSD Duplicator and Sanitizer



MTS-SAS series is a professional SAS/SATA HDD duplicator and data eraser, specially designed for handling high volume devices. U-Reach adopted a unique multitasking technology that can copy or erase up to 15 targets with a high transfer speed of 30 GB per minute. We guarantee the highest productivity without speed degradation, even as the number of targets increase.

Features

Operation Type

Stand-alone, FPGA-based operation (Non PC-based system design).

Bandwidth Performance

Speed transfers of up to 30.0GB/min. (500MB/sec.) Dedicated bandwidth enables high-volume erase or replications without speed degradation.

Modular Socket Design

Modular-designed ports effectively reduce downtime and is cost-effective for long-term ownership.




Real-Time PC Monitoring

View live status for: writing/reading speed, total capacity, current function progress per port.

Event Log Management

- Records: operating durations, individual port copy progressions, connected device models, capacities, serial numbers, and PASS or FAIL results.
- Device writing/reading speeds are recorded.
- Log report files are generated through Port #1 or through the U-Reach PC Link Software Utility.

Product Models

Photos	Models	Target Ports	Product Dimensions	Package Dimensions	Package Weight
	MTS-400SAS	1:3	39.3 x 22 x 21 cm	51 x 32.7 x 31.2 cm	7 Kg
	MTS-800SAS	1:7	39.3 x 40 x 21 cm	53 x 52 x 39 cm	13.5 Kg
	MTS-1600SAS	1:15	60.5 x 38 x 44.2 cm	74 x 51 x 45 cm	23 Kg

Standard Package



Duplicator x 1



Power Cord x 1




Grounding Cable x 1



USB Cable for PC Link x 1



PC Link Software Disc x 1



User Manual x 1

Optional Accessories

TB1534




SAS Cable

P1041



mSATA Adapter

P1040



microSATA
Adapter

P1050V2



M.2 (NGFF)
Adapter

P1053



CFast
Adapter

TB1602



SATA DOM
Adapter*

*There are 3 types of power supply for SATA DOM cards. Please double check before purchase.

Specifications

Maximum Speed Supported	30.0GB/min *Actual performance is dependent on device transfer speeds*
Supported Capacity	Up to 18TB.
Operation Mode	Standalone, FPGA-based Operation
Language	English, Japanese
Erase	<ul style="list-style-type: none"> • 10 Erase Modes. • Asynchronous and Synchronous Erase. • Support Erase HPA.
Copy	<ul style="list-style-type: none"> • Quick Copy (System and Files): FAT16/32/exFAT, Windows (NTFS), Linux(Ext2/Ext3/Ext4), and Mac(HFS/HFS+/HFSX) • Whole Device Copy: All formats, including proprietary formats. • GPT, MBR, and Advanced Formats.
Supported OS	All (Windows, Mac, Linux, and other proprietary systems)

Functions

Sanitization Modes	Full Erase(1-Pass Erase), DoD Erase, 7-Pass Erase, Secure Erase, US Army AR 380-19, BMB21-2007, Sanitize Block Erase and Sanitize Purge.
Copy Modes	Quick Copy (System and Files) / All Partitions / Whole Device / Percentage Copy
Compare (Verification)	Bit-by-bit data comparison from the source device to target device(s).
Skip Bad Sectors	Skip the number of bad sectors during Erase/Copy/Compare.
Minimum Speed	Disable or set minimum threshold speed to drop the slowest device.
Clear HPA at Erase	Keep or clear HPA settings during sanitization process.
HPA Copy Modes	Allows user to choose various HPA replication methods.
Log Manager	Manage and export log reports.
Others	Copy/Skip Unknow Format, Erase Source Port, Transfer Modes, Device Power-up/down Time.

Compatibilities

Compatible Device	2.5"/3.5" HDD and SSDs.
Devices Require Optional Cables or Adapters	mSATA, microSATA, eSATA, M.2(NGFF), CFast, SATA DOM
Compatible Protocol	SAS, SATA

Hardware Specifications

LCD Display	2x20 Backlit Monochrome LCD Display	
LEDs	3 LED Indicators per Port: Yellow (Power), Green (Pass), Red (Fail)	
Control Panel	4 Push Buttons (▲, ▼, OK, ESC), 1 Fast Key for Asynchronous Erase	
Power Requirements	Universal Power: 115V AC or 230V AC, 50/60Hz	
Temperature	Working: 0°C ~ 60°C	Storage: -20°C ~ 85°C
Humidity	Working: 20% ~ 80%	Storage: 5% ~ 95%
Certifications	FCC, CE, RoHS, and Reach	

****Specifications subject to change without notice.**